

# UNCLASSIFIED

AD NUMBER
AD842431
NEW LIMITATION CHANGE
TO Approved for public release, distribution unlimited
FROM Distribution authorized to U.S. Gov't. agencies and their contractors; Administrative/Operational Use; OCT 1968. Other requests shall be referred to the U. S. Army Electronics Command, Ft. Monmouth, New Jersey.
AUTHORITY
st-a usaec notice, dtd 13 Sep 1971

THIS PAGE IS UNCLASSIFIED

AD 842431

THIS DOCUMENT IS SUBJECT TO SPECIAL EXPORT CONTROLS AND EACH TRANSMITTAL TO FOREIGN GOVERNMENTS OR FOREIGN NATIONALS MAY BE MADE ONLY WITH PRIOR APPROVAL OF ATMOSPHERIC SCIENCE RESEARCH OFFICE, WHITE SANDS MISSILE RANGE, NEW MEXICO.

DR-358  
October 1968

AD

METEOROLOGICAL DATA REPORT

NIKE-HYDAC STV, SR-073  
(5 September 1968)

BY

GORDON L. DUNAWAY

ATMOSPHERIC SCIENCE RESEARCH OFFICE  
WHITE SANDS MISSILE RANGE, NEW MEXICO

.....  
**ECOM**

UNITED STATES ARMY ELECTRONICS COMMAND

DDC  
RECEIVED  
NOV 5 1968  
RECEIVED  
C

ACCESSION No.	
CESTI	WHITE SECTION <input type="checkbox"/>
DOC	BOYF SECTION <input checked="" type="checkbox"/>
EXAMINER	<input type="checkbox"/>
JUSTIFICATION	
BY	
DISTRIBUTION/AVAILABILITY CODES	
DXT.	AVAIL. AND/OR SPECIAL
2	

### DISPOSITION INSTRUCTIONS

Destroy this report when it is no longer needed. Do not return it to the originator.

### DISCLAIMER

The findings in this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The citation of trade names and names of manufacturers in this report is not to be construed as official Government endorsement or approval of commercial products or services referenced herein.

METEOROLOGICAL DATA REPORT

NIKE-HYDAC STV, SR-073  
(5 September 1968)

By

Gordon L. Dunaway

DR-358

October 1968

DA Task 1T665702D127-02

ATMOSPHERIC SCIENCE RESEARCH OFFICE  
WHITE SANDS MISSILE RANGE, NEW MEXICO

This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of Atmospheric Science Research Office, White Sands Missile Range, New Mexico.

#### ABSTRACT

Meteorological data gathered for the launching of Nike-Hydac STV, SR-073, are presented for the Space and Missile Systems Organization and for ballistic studies. The data appear, along with calculated ballistic data, in tabular form.

## CONTENTS

	PAGE
ABSTRACT -----	111
INTRODUCTION -----	1
DISCUSSION -----	1
TABLES	
I. Theoretical Rocket Performance Values -----	2
II. Ballistic Factors -----	3
III. Anemometer Wind Speed and Direction -----	4
IV. Pilot-Balloon-Measured Wind Data -----	5
V. Rawinsonde-Measured Wind Data -----	7
VI. Significant Level Data (Release Time: 0300 MDT) -----	8
VII. Upper Air Data (Release Time: 0300 MDT) -----	9
VIII. Mandatory Levels (Release Time: 0300 MDT) -----	17
IX. Significant Level Data (Release Time: 0530 MDT) -----	18
X. Upper Air Data (Release Time: 0530 MDT) -----	20
XI. Mandatory Levels (Release Time: 0530 MDT) -----	28
XII. Impact Prediction Data -----	29

## INTRODUCTION

Nike-Hydac STV, SR-073, was launched from LC-33, L-314, White Sands Missile Range (WSMR), New Mexico, at 0600 hours MDT, 5 September 1968.

Meteorological data used in conjunction with theoretical calculations to predict rocket impact were collected by the Meteorological Support Technical Area, U. S. Army Electronics Research and Development Activity, WSMR, New Mexico. The Ballistics Meteorologists for this firing were Gordon L. Dunaway and Dennis E. Hulse.

## DISCUSSION

Wind data for the first 216 feet above the surface were obtained from a system composed of five Aerovanes mounted on a 200-foot tower and cabled to two component wind indicators for each level.

From 216 to 4,000 feet above the surface, wind data were obtained from T-9 radar tracked balloon ascents.

Temperature, pressure, and humidity data, along with upper wind data from 4,000 to 100,000 feet above the surface, were obtained from standard rawinsonde observations.

Mean wind component values in each ballistic zone were determined from vertical cross sections by the equal-area method.

Theoretical rocket performance values and wind-weighting values as a function of altitude were provided by the Meteorological Support Technical Area, WSMR, New Mexico, and are the basis for the data appearing in Table I.

PAYLOAD		218	Pounds
CORIOIIS DISPLACEMENT	WEST	4.9	Miles
SECOND-STAGE IGNITION	TIME	20.0	Seconds
	ALTITUDE	35,760	Feet MSL
PEAK	TIME	236	Seconds
	ALTITUDE	716,000	Feet MSL
UNIT WIND EFFECT	HEAD	2.51	Miles/MPH
	CROSS	2.60	Miles/MPH
	TAIL	2.52	Miles/MPH
TOWER TILT EFFECT		14.53	Miles/Degree

TABLE I. THEORETICAL ROCKET PERFORMANCE VALUES  
NIKE-HYDAC STV, SR-073



LAYERS IN FEET ABOVE GROUND	BALLISTIC FACTORS
15- 60	.126
60- 108	.084
108- 418	.053
148- 184	.041
184- 216	.026
216- 300	.062
300- 400	.059
400- 600	.072
600- 800	.058
800-1000	.039

LAYERS IN FEET ABOVE GROUND	BALLISTIC FACTORS
1000- 1400	.063
1400- 2000	.066
2000- 2500	.025
2500- 3000	.028
3000- 3500	.014
3500- 4000	.005
4000- 4160	-.003
4160- 9000	-.014
9000-15000	-.017
15000-21000	-.016

LAYERS IN FEET ABOVE GROUND	BALLISTIC FACTORS
21000-26000	-.013
26000-31770	-.016
31770-36000	.129
36000-41000	.057
41000-46000	.026
46000-51000	.015
51000-56000	.010
56000-61000	.006
61000-66000	.004
66000-69330	.002

TABLE II. BALLISTIC FACTORS  
NIKE-HYDAC STV, SR-073

AERO- VANE NO. *	MEAN WIND COMPONENTS IN MILES PER HOUR									
	1 0400 MDT		2 0430 MDT		3 0500 MDT		4 0515 MDT		5 0530 MDT	
	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W
	1	7.0S	8.0E	5.0S	5.0E	1.0S	3.0E	0.0	4.0W	0.0
2	10.0	10.0	5.0	6.0	1.0	4.0	0.0	5.0	0.0	4.0
3	6.0	15.0	5.0	11.0	2.0	3.0	1.0S	4.0	0.0	3.0
4	10.0	12.0	10.0	10.0	1.0	2.0	1.0	3.0	0.0	2.0
5	11.0	12.0	8.0	9.0	2.0	2.0	1.0	4.0	0.0	2.5

AERO- VANE NO. *	MEAN WIND COMPONENTS IN MILES PER HOUR							
	6 0540 MDT		7 0550 MDT		8 0600 MDT			
	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W
	1	0.0	3.0W	0.0	2.0W	0.0	0.0	
2	0.0	4.0	0.0	3.0	0.0	2.0W		
3	0.0	3.0	0.0	3.0	2.0S	2.0		
4	0.0	3.0	0.0	2.0	3.0	2.0		
5	0.0	3.0	0.0	2.0	2.0	2.0		

TABLE III. ANEMOMETER WIND SPEED AND DIRECTION  
NIKE-HYDAC STV, SR-073

\* Heights corresponding to Aerovane Numbers: 1 = 35 Feet 3 = 128 Feet 5 = 200 Feet  
2 = 88 Feet 4 = 168 Feet

LAYERS IN FEET ABOVE GROUND	MEAN WIND COMPONENTS IN MILES PER HOUR									
	1 0400 MDT		2 0430 MDT		3 0500 MDT		4 0515 MDT		5 0530 MDT	
	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W
216- 300	11.5S	12.5E	8.0S	9.0E	2.0S	4.0E	1.0S	3.0W	0.5S	2.5W
300- 400	12.5	14.0	9.5	9.5	5.0	4.5	3.0	1.0	2.0	2.0
400- 600	13.5	14.5	12.5	10.5	8.0	6.0	5.0	0.5E	2.0	1.5
600- 800	10.0	14.0	13.0	13.5	11.0	11.5	7.0	2.5	4.5	2.0E
800-1000	8.0	8.0	14.0	10.5	9.0	8.0	10.0	9.0	5.0	8.0
1000-1400	8.0	2.0	5.0	5.0	8.0	1.5	7.5	8.5	8.0	9.5
1400-2000	10.5	4.0W	8.0	0.0	10.0	1.5W	9.0	4.0	6.5	4.0
2000-2500	14.0	2.0E	12.0	0.5W	15.0	1.0E	16.0	1.0W	10.5	2.0W
2500-3000	19.5	5.0	22.5	1.0E	17.0	1.5W	22.5	1.0E	16.0	0.0
3000-3500	27.0	5.0	24.0	0.0	20.0	2.0	17.0	2.5W	21.0	3.5W
3500-4000	24.0	0.0	16.5	2.0W	24.0	2.5	12.5	3.5	13.5	3.0

TABLE IV. PILOT-BALLOON-MEASURED WIND DATA  
NIKE-HYDAC STV, SR-073

LAYERS IN FEET ABOVE GROUND	MEAN WIND COMPONENTS IN MILES PER HOUR									
	6		7		8					
	0540 MDT		0550 MDT		0600 MDT					
	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W
216- 300	0.0	1.5W	1.0S	0.5W	2.0S	1.0W				
300- 400	0.5N	0.0	1.5	0.5E	3.5	0.5				
400- 600	3.0S	0.5W	3.0	1.0	2.0	1.0E				
600- 800	2.0	0.0	1.5	2.5	4.5	4.5				
800-1000	0.0	3.5E	3.5	6.5	5.0	7.5				
1000-1400	6.0S	11.0	7.0	10.5	8.0	12.0				
1400-2000	7.0	6.0	6.0	6.0	9.5	10.5				
2000-2500	13.0	1.0W	9.0	0.5W	7.0	2.5				
2500-3000	13.0	0.5	15.0	0.5E	12.0	0.5				
3000-3500	20.0	5.0	21.0	3.0W	20.0	1.5W				
3500-4000	10.0	7.0	14.5	5.0	16.0	5.5				

TABLE IV. PILOT-BALLOON-MEASURED WIND DATA (CONT)  
NIKE-HYDAC STV, BR-073

LAYERS IN FEET ABOVE GROUND	MEAN WIND COMPONENTS IN KNOTS					
	1		2			
	0300 MDT		0530 MDT			
	N-S	E-W	N-S	E-W	N-S	E-W
4000-4160	13.0S	5.0W	8.0S	4.5W		
4160-9000	4.5	8.0	0.0	7.0		
9000-15000	9.0N	1.5	4.5N	4.0		
15000-21000	10.5	12.5	9.5	11.5		
21000-26000	10.5	18.5	13.5	16.0		
26000-31770	16.0	28.0	5.0	27.5		
31770-36000	3.0	34.0	3.0S	32.5		
36000-41000	0.0	40.0	6.5	35.5		
41000-46000	5.0S	27.5	0.0	27.0		
46000-51000	3.0	15.5	3.0N	18.0		
51000-56000	0.0	10.0	2.5S	13.0		
56000-61000	1.5S	10.0	6.0	0.0		
61000-66000	3.0N	5.0	6.5N	11.5E		
66000-69330	10.5	12.0E	3.0	18.0		

TABLE V. RAWINSONDE-MEASURED WIND DATA  
NIKE-HYDAC STV, SR-073

SIGNIFICANT LEVEL DATA  
0312003907  
WHITE SANDS SITE

STATION ALTITUDE 3989.0 FEET MSL  
5 SEPT.68 0300 HRS MDT  
ASCENSION NO. 722

TABLE VI

PRESSURE		GEOMETRIC ALTITUDE		TEMPERATURE		REL. HUM.
MILLIBARS	MSL FEET	AIR DEGREES	DEWPOINT CENTIGRADE	AIR DEGREES	PERCENT	
881.5	3989.0	20.0	13.6	20.0	66.0	
872.0	4296.5	20.3	11.3	20.3	56.0	
798.0	6794.4	16.0	8.1	16.0	59.0	
753.0	8413.3	15.0	3.5	15.0	46.0	
655.0	12227.8	5.5	-2.8	5.5	55.0	
600.0	14557.3	-1.4	-4.4	-1.4	80.0	
581.0	15398.4	-3.1	-9.4	-3.1	62.0	
553.0	16677.4	-6.3	-9.9	-6.3	76.0	
533.0	17626.1	-5.7	-25.2	-5.7	20.0	
477.0	20452.0	-12.1	-30.1	-12.1	21.0	
461.0	21309.3	-12.6	-32.1	-12.6	18.0	
400.0	24812.2	-21.4	-39.0	-21.4	19.0	
319.0	30155.8	-34.8	-50.0	-34.8	20.0	
249.0	35683.8	-48.6	0.	-48.6	-0.	**
217.0	38621.4	-54.9	0.	-54.9	-0.	**
144.0	47043.2	-65.7	0.	-65.7	-0.	**
132.0	48792.9	-64.1	0.	-64.1	-0.	**
112.0	52068.9	-69.3	0.	-69.3	-0.	**
100.0	54331.4	-63.7	0.	-63.7	-0.	**
55.0	66529.2	-60.3	0.	-60.3	-0.	**
40.0	73176.0	-54.5	0.	-54.5	-0.	**
24.0	84059.9	-51.6	0.	-51.6	-0.	**
17.5	90954.1	-44.2	0.	-44.2	-0.	**
10.0	103437.7	-42.0	0.	-42.0	-0.	**
5.9	115329.3	-40.0	0.	-40.0	-0.	**

## RELATIVE HUMIDITY NOT SUPPLIED. ZERO VALUE ASSUMED FOR COMPUTATIONS.

STATION ALTITUDE 3989.0 FEET MSL  
5 SEPT. 68 0300 HRS MDT  
ASCENSION NO. 722

UPPER AIR DATA  
0312003907  
WHITE SANDS SITE

WSTM SITE COORDINATES  
E 488.580 FEET  
N 185.045 FEET

TABLE VII

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND		WIND DATA DIRECTION DEGREES(TN)	SPEED KNOTS	INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE			KNOTS	KNOTS			
3989.0	881.5	20.0	13.6	66.0	1040.8	668.9		100.0	6.0	1.000300
4000.0	881.2	20.0	13.5	65.6	1040.3	668.9		100.5	6.0	1.000300
4500.0	865.7	19.9	11.1	56.2	1023.2	668.5		121.5	6.8	1.000286
5000.0	850.5	19.1	10.4	56.8	1008.3	667.5		142.6	7.6	1.000280
5500.0	835.5	18.2	9.8	57.4	993.7	666.5		163.7	8.4	1.000275
6000.0	820.8	17.4	9.1	58.0	979.2	665.4		181.7	9.5	1.000270
6500.0	806.4	16.5	8.4	58.6	955.0	664.4		186.8	12.2	1.000265
7000.0	792.1	15.9	7.5	57.3	950.2	663.6		189.6	13.7	1.000259
7500.0	778.1	15.6	6.2	53.3	934.7	663.1		191.2	14.5	1.000251
8000.0	764.2	15.3	4.7	49.3	919.4	662.7		199.1	13.0	1.000244
8500.0	750.6	14.8	3.4	46.2	904.7	662.0		211.2	11.3	1.000237
9000.0	737.0	13.5	2.6	47.4	892.3	660.5		227.9	9.6	1.000233
9500.0	723.7	12.3	1.8	48.6	880.1	659.1		236.7	9.4	1.000228
10000.0	710.6	11.0	1.0	49.7	868.1	657.6		242.0	9.2	1.000224
10500.0	697.7	9.8	0.1	50.9	856.2	656.1		241.6	8.6	1.000220
11000.0	685.1	8.6	-0.7	52.1	844.6	654.6		242.4	7.3	1.000216
11500.0	672.7	7.3	-1.6	53.3	833.1	653.1		243.9	5.7	1.000212
12000.0	660.5	6.1	-2.4	54.5	821.8	651.6		260.6	4.1	1.000208
12500.0	648.3	4.7	-2.9	57.9	810.7	650.0		281.9	2.4	1.000205
13000.0	636.2	3.2	-3.1	63.3	799.8	648.2		317.8	2.9	1.000202
13500.0	624.4	1.7	-3.4	68.7	789.1	646.5		355.4	3.6	1.000200
14000.0	612.7	0.3	-3.8	74.0	778.6	644.7		2.8	4.8	1.000197
14500.0	601.3	-1.2	-4.4	79.4	768.3	643.0		9.0	6.1	1.000194
15000.0	589.9	-2.3	-7.0	70.5	757.1	641.6		6.6	7.1	1.000187
15500.0	578.7	-3.4	-9.4	63.1	745.9	640.2		3.4	8.0	1.000182
16000.0	567.7	-4.6	-9.5	68.6	735.0	638.7		356.8	8.5	1.000179
16500.0	556.8	-5.9	-9.8	74.1	724.3	637.2		346.8	9.1	1.000177
17000.0	546.1	-6.1	-13.3	57.0	711.4	636.8		330.6	9.6	1.000170
17500.0	535.6	-5.8	-21.7	27.4	697.4	636.9		318.1	10.4	1.000161
18000.0	525.2	-6.5	-25.8	20.1	686.0	635.9		308.2	11.5	1.000157

WSTM SITE COORDINATES  
E 488.580 FEET  
N 185.045 FEET

UPPER AIR DATA  
0312003907  
WHITE SANDS SITE

STATION ALTITUDE 3989.0 FEET MSL  
5 SEPT.68 0300 HRS MDT  
ASCENSION NO. 722

TABLE VII (Cont).

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND		WIND DATA DIRECTION DEGREES(TN)	SPEED KNOTS	INDEX OF REFRACTION
		AIR DEGREES CENTIGRADE	DEWPOINT CENTIGRADE			KNOTS	KNOTS			
18500.0	515.0	-7.7	-26.7	20.3	675.6	634.6	302.2	302.2	13.2	1.000154
19000.0	505.0	-8.8	-27.5	20.5	655.3	633.2	297.8	297.8	14.8	1.000152
19500.0	495.2	-9.9	-28.4	20.7	655.2	631.9	302.2	302.2	15.2	1.000149
20000.0	485.5	-11.1	-29.3	20.8	645.2	630.5	306.3	306.3	15.6	1.000147
20500.0	476.1	-12.1	-30.2	20.8	635.2	629.2	309.9	309.9	16.0	1.000144
21000.0	466.7	-12.4	-31.3	19.1	623.4	628.8	313.3	313.3	16.4	1.000141
21500.0	457.5	-13.1	-32.5	18.1	612.6	628.0	316.1	316.1	16.5	1.000139
22000.0	448.3	-14.3	-33.4	18.2	603.3	626.5	317.8	317.8	16.5	1.000136
22500.0	439.3	-15.6	-34.4	18.3	594.1	625.0	318.1	318.1	16.2	1.000134
23000.0	430.5	-16.8	-35.4	18.5	585.0	623.5	316.6	316.6	16.5	1.000132
23500.0	421.8	-18.1	-36.4	18.6	576.1	621.9	313.1	313.1	17.3	1.000130
24000.0	413.4	-19.4	-37.4	18.8	557.4	620.4	310.5	310.5	17.8	1.000128
24500.0	405.1	-20.6	-38.4	18.9	558.8	618.8	308.9	308.9	18.0	1.000126
25000.0	396.8	-21.9	-39.4	19.0	550.1	617.3	306.5	306.5	18.7	1.000124
25500.0	388.5	-23.1	-40.4	19.1	541.3	615.7	303.3	303.3	19.8	1.000122
26000.0	380.4	-24.4	-41.4	19.2	532.7	614.2	301.5	301.5	20.2	1.000120
26500.0	372.4	-25.6	-42.4	19.3	524.1	612.6	300.7	300.7	20.1	1.000118
27000.0	364.6	-26.9	-43.5	19.4	515.8	611.1	299.8	299.8	20.9	1.000116
27500.0	357.0	-28.1	-44.5	19.5	507.6	609.5	298.9	298.9	22.3	1.000114
28000.0	349.5	-29.4	-45.5	19.6	499.5	608.0	298.1	298.1	23.0	1.000112
28500.0	342.2	-30.6	-46.5	19.7	491.6	606.4	297.6	297.6	22.9	1.000110
29000.0	335.0	-31.9	-47.6	19.8	483.8	604.8	297.2	297.2	23.4	1.000108
29500.0	328.0	-33.2	-48.6	19.9	476.1	603.2	297.1	297.1	24.8	1.000107
30000.0	321.1	-34.4	-49.7	20.0	468.6	601.7	296.9	296.9	25.7	1.000105
30500.0	314.1	-35.7	-51.3	18.8**	460.8	600.1	296.6	296.6	25.2	1.000103
31000.0	307.2	-36.9	-53.2	16.9**	453.0	598.5	296.3	296.3	25.4	1.000101
31500.0	300.4	-38.2	-55.2	15.1**	445.3	596.9	296.1	296.1	26.6	1.000099
32000.0	293.7	-39.4	-57.2	13.3**	437.8	595.3	295.7	295.7	26.7	1.000098
32500.0	287.2	-40.7	-59.4	11.5**	430.4	593.7	295.1	295.1	26.0	1.000096
33000.0	280.8	-41.9	-61.8	9.7**	423.1	592.1	294.3	294.3	27.3	1.000094

\*\* AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.



STATION ALTITUDE 3989.0 FEET MSL  
5 SEPT. 68 0300 HRS EDT  
ASCENSION NO. 722

UPPER AIR DATA  
0312003907  
WHITE SANDS SITE

WSTM SITE COORDINATES  
E 488.580 FEET  
N 185.045 FEET

TABLE VII (Cont)

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND		WIND DATA		INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE			KNOTS	KNOTS	DIRECTION DEGREES(TN)	SPEED KNOTS	
33500.0	274.6	-43.1	-64.3	7.9**	416.0	590.5	293.4	293.4	29.5	1.000093
34000.0	268.5	-44.4	-67.2	6.1**	409.0	583.9	291.8	291.8	30.8	1.000091
34500.0	262.6	-45.6	-70.6	4.3**	402.1	587.3	290.0	290.0	32.2	1.000090
35000.0	256.7	-46.9	-75.2	2.5**	395.4	585.7	288.0	288.0	33.8	1.000088
35500.0	251.1	-48.1	-84.0	0.7**	388.8	584.1	285.5	285.5	34.7	1.000087
36000.0	245.3	-49.3	0.	-0. **	381.8	582.6	282.3	282.3	34.3	1.000085
36500.0	239.7	-50.4	0.	-0. **	374.8	581.2	279.3	279.3	34.0	1.000083
37000.0	234.1	-51.4	0.	-0. **	367.9	579.8	276.6	276.6	33.9	1.000082
37500.0	228.7	-52.5	0.	-0. **	361.1	578.4	273.2	273.2	34.0	1.000080
38000.0	223.4	-53.6	0.	-0. **	354.5	577.0	268.4	268.4	34.2	1.000079
38500.0	218.2	-54.6	0.	-0. **	348.0	575.6	264.5	264.5	34.8	1.000077
39000.0	213.0	-55.4	0.	-0. **	340.8	574.6	262.9	262.9	36.5	1.000076
39500.0	207.9	-56.0	0.	-0. **	333.6	573.8	261.8	261.8	38.2	1.000074
40000.0	202.9	-56.7	0.	-0. **	326.6	572.9	261.6	261.6	40.3	1.000073
40500.0	198.0	-57.3	0.	-0. **	319.7	572.1	262.1	262.1	42.4	1.000071
41000.0	193.3	-58.0	0.	-0. **	312.9	571.2	263.5	263.5	44.7	1.000070
41500.0	188.6	-58.6	0.	-0. **	306.3	570.4	265.1	265.1	45.8	1.000068
42000.0	184.1	-59.2	0.	-0. **	299.8	569.5	266.9	266.9	44.6	1.000067
42500.0	179.7	-59.9	0.	-0. **	293.5	568.6	268.5	268.5	43.2	1.000065
43000.0	175.3	-60.5	0.	-0. **	287.3	567.8	269.3	269.3	41.4	1.000064
43500.0	171.1	-61.2	0.	-0. **	281.2	566.9	270.1	270.1	39.5	1.000063
44000.0	167.0	-61.8	0.	-0. **	275.3	566.1	269.1	269.1	37.1	1.000061
44500.0	163.0	-62.4	0.	-0. **	269.5	565.2	267.9	267.9	34.5	1.000060
45000.0	159.1	-63.1	0.	-0. **	263.8	564.4	266.1	266.1	32.7	1.000059
45500.0	155.2	-63.7	0.	-0. **	258.3	563.5	263.7	263.7	31.9	1.000058
46000.0	151.5	-64.4	0.	-0. **	252.8	562.6	261.3	261.3	31.2	1.000056
46500.0	147.9	-65.0	0.	-0. **	247.5	561.8	260.2	260.2	30.8	1.000055
47000.0	144.3	-65.6	0.	-0. **	242.3	560.9	259.5	259.5	30.4	1.000054
47500.0	140.8	-65.3	0.	-0. **	235.9	561.4	258.9	258.9	30.1	1.000053
48000.0	137.3	-64.8	0.	-0. **	229.6	562.0	261.9	261.9	29.4	1.000051

\*\* AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL  
5 SEPT. 68 0300 HRS MDT  
ASCENSION NO. 722

UPPER AIR DATA  
0312003907  
WHITE SANDS SITE

WSTM SITE COORDINATES  
E 488.580 FEET  
N 185.045 FEET

TABLE VII (Cont)

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA		INDEX OF REFRACTION
		AIR DEGREES CENTIGRADE	DEWPOINT CENTIGRADE				DIRECTION DEGREES(TN)	SPEED KNOTS	
48500.0	133.9	-64.4	0.	-0. **	223.5	562.6	265.0	28.6	1.000050
49000.0	130.6	-64.4	0.	-0. **	218.1	562.5	268.0	27.9	1.000049
49500.0	127.4	-65.2	0.	-0. **	213.5	561.5	268.6	25.8	1.000048
50000.0	124.2	-66.0	0.	-0. **	209.0	560.4	269.2	23.7	1.000047
50500.0	121.2	-66.8	0.	-0. **	204.6	559.3	269.9	21.6	1.000046
51000.0	118.2	-67.6	0.	-0. **	200.3	558.2	269.8	21.3	1.000045
51500.0	115.2	-68.4	0.	-0. **	196.1	557.2	269.6	21.3	1.000044
52000.0	112.4	-69.2	0.	-0. **	192.0	556.1	269.4	21.4	1.000043
52500.0	109.6	-68.2	0.	-0. **	186.4	557.4	267.3	20.2	1.000041
53000.0	106.9	-67.0	0.	-0. **	180.7	559.1	263.0	17.6	1.000040
53500.0	104.3	-65.8	0.	-0. **	175.1	560.7	258.8	15.0	1.000039
54000.0	101.7	-64.5	0.	-0. **	159.8	562.4	254.5	12.5	1.000038
54500.0	99.2	-63.7	0.	-0. **	164.9	563.6	257.4	12.3	1.000037
55000.0	96.8	-63.5	0.	-0. **	150.8	563.8	260.8	12.2	1.000036
55500.0	94.4	-63.4	0.	-0. **	156.8	564.0	264.1	12.2	1.000035
56000.0	92.1	-63.2	0.	-0. **	152.9	564.2	262.6	11.6	1.000034
56500.0	89.9	-63.1	0.	-0. **	149.1	564.3	252.2	9.9	1.000033
57000.0	87.7	-63.0	0.	-0. **	145.4	564.5	241.7	8.3	1.000032
57500.0	85.6	-62.8	0.	-0. **	141.8	564.7	231.2	6.6	1.000032
58000.0	83.5	-62.7	0.	-0. **	138.3	564.9	236.3	7.0	1.000031
58500.0	81.5	-62.5	0.	-0. **	134.9	565.1	246.7	8.1	1.000030
59000.0	79.5	-62.4	0.	-0. **	131.5	565.3	257.0	9.2	1.000029
59500.0	77.6	-62.3	0.	-0. **	128.2	565.5	264.2	10.0	1.000029
60000.0	75.7	-62.1	0.	-0. **	125.1	565.6	253.1	9.6	1.000028
60500.0	73.9	-62.0	0.	-0. **	121.9	565.8	242.0	9.3	1.000027
61000.0	72.1	-61.8	0.	-0. **	118.9	566.0	230.9	8.9	1.000026
61500.0	70.4	-61.7	0.	-0. **	116.0	566.2	224.2	8.4	1.000026
62000.0	68.7	-61.6	0.	-0. **	113.1	566.4	221.3	7.8	1.000025
62500.0	67.0	-61.4	0.	-0. **	110.3	566.6	218.4	7.3	1.000025
63000.0	65.4	-61.3	0.	-0. **	107.5	566.8	215.5	6.7	1.000024

\*\* AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL

5 SEPT. 68

ASCENSION NO. 722

UPPER AIR DATA

0312003907

WHITE SANDS SITE

WSTM SITE COORDINATES

E 488.580 FEET

N 185.045 FEET

TABLE VII (Cont)

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND		WIND DIRECTION DEGREES (TN)	WIND SPEED KNOTS	INDEX OF REFRACTION
		AIR DEGREES CENTIGRADE	DEWPOINT CENTIGRADE			SOUND KNOTS	OF			
63500.0	63.8	-61.1	0.	-0. **	104.9	567.0		211.0	7.0	1.000023
64000.0	62.3	-61.0	0.	-0. **	102.2	567.1		206.4	7.4	1.000023
64500.0	60.8	-60.9	0.	-0. **	99.7	567.3		201.7	7.8	1.000022
65000.0	59.3	-60.7	0.	-0. **	97.2	567.5		197.1	8.1	1.000022
65500.0	57.8	-60.6	0.	-0. **	94.8	567.7		209.1	7.3	1.000021
66000.0	56.4	-60.4	0.	-0. **	92.5	567.9		222.3	6.3	1.000021
66500.0	55.1	-60.3	0.	-0. **	90.2	568.1		235.5	5.3	1.000020
67000.0	53.8	-59.9	0.	-0. **	87.9	568.6		248.7	4.3	1.000020
67500.0	52.5	-59.5	0.	-0. **	85.8	569.2		263.8	4.6	1.000019
68000.0	51.3	-59.0	0.	-0. **	83.4	569.8		279.9	5.6	1.000019
68500.0	50.0	-58.6	0.	-0. **	81.3	570.4		296.1	6.6	1.000018
69000.0	48.9	-58.1	0.	-0. **	79.2	570.9		312.2	7.5	1.000018
69500.0	47.7	-57.7	0.	-0. **	77.1	571.5		327.4	8.4	1.000017
70000.0	46.6	-57.3	0.	-0. **	75.2	572.1		340.5	8.9	1.000017
70500.0	45.5	-56.8	0.	-0. **	73.2	572.7		353.6	9.4	1.000016
71000.0	44.4	-56.4	0.	-0. **	71.4	573.3		6.7	9.9	1.000016
71500.0	43.3	-56.0	0.	-0. **	69.5	573.8		19.6	10.4	1.000015
72000.0	42.3	-55.5	0.	-0. **	67.8	574.4		31.6	10.9	1.000015
72500.0	41.3	-55.1	0.	-0. **	66.0	575.0		43.6	11.4	1.000015
73000.0	40.3	-54.7	0.	-0. **	64.3	575.6		55.5	11.9	1.000014
73500.0	39.4	-54.4	0.	-0. **	62.8	575.9		63.7	12.8	1.000014
74000.0	38.5	-54.3	0.	-0. **	61.3	576.1		65.3	14.2	1.000014
74500.0	37.6	-54.1	0.	-0. **	59.8	576.2		66.9	15.6	1.000013
75000.0	36.7	-54.0	0.	-0. **	58.4	576.4		68.5	17.0	1.000013
75500.0	35.9	-53.9	0.	-0. **	57.0	576.6		70.4	18.1	1.000013
76000.0	35.0	-53.7	0.	-0. **	55.6	576.8		72.4	19.1	1.000012
76500.0	34.2	-53.6	0.	-0. **	54.3	576.9		74.4	20.1	1.000012
77000.0	33.4	-53.5	0.	-0. **	53.0	577.1		75.2	20.7	1.000012
77500.0	32.7	-53.3	0.	-0. **	51.8	577.3		75.4	21.2	1.000012
78000.0	31.9	-53.2	0.	-0. **	50.5	577.5		75.7	21.7	1.000011

\*\* AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL  
5 SEPT. 68 0300 HRS MDT  
ASCENSION NO. 722

UPPER AIR DATA  
0312003907  
WHITE SANDS SITE

WSTM SITE COORDINATES  
E 488.580 FEET  
N 185.045 FEET

TABLE VII (Cont)

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND		WIND DATA		INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE			KNOTS	KNOTS	DIRECTION DEGREES(TN)	SPEED KNOTS	
78500.0	31.2	-53.1	0.	-0. **	49.3	577.6	77.4	22.5	1.000011	
79000.0	30.4	-52.9	0.	-0. **	48.2	577.8	82.0	24.2	1.000011	
79500.0	29.7	-52.8	0.	-0. **	47.0	578.0	86.6	25.9	1.000010	
80000.0	29.0	-52.7	0.	-0. **	45.9	578.2	91.2	27.6	1.000010	
80500.0	28.4	-52.5	0.	-0. **	44.8	578.3	94.1	26.2	1.000010	
81000.0	27.7	-52.4	0.	-0. **	43.7	578.5	97.0	24.6	1.000010	
81500.0	27.1	-52.3	0.	-0. **	42.7	578.7	99.9	23.1	1.000010	
82000.0	26.4	-52.1	0.	-0. **	41.7	578.9	100.1	21.8	1.000009	
82500.0	25.8	-52.0	0.	-0. **	40.7	579.0	98.8	20.6	1.000009	
83000.0	25.2	-51.9	0.	-0. **	39.7	579.2	97.6	19.5	1.000009	
83500.0	24.6	-51.7	0.	-0. **	38.8	579.4	98.1	18.6	1.000009	
84000.0	24.1	-51.6	0.	-0. **	37.9	579.6	100.4	18.1	1.000008	
84500.0	23.5	-51.1	0.	-0. **	36.9	580.2	102.8	17.6	1.000008	
85000.0	23.0	-50.6	0.	-0. **	35.0	580.9	103.2	17.5	1.000008	
85500.0	22.5	-50.1	0.	-0. **	35.1	581.6	100.5	18.1	1.000008	
86000.0	22.0	-49.5	0.	-0. **	34.2	582.3	97.8	18.8	1.000008	
86500.0	21.5	-49.0	0.	-0. **	33.4	583.0	96.0	19.3	1.000007	
87000.0	21.0	-48.4	0.	-0. **	32.5	583.7	97.0	19.7	1.000007	
87500.0	20.5	-47.9	0.	-0. **	31.7	584.4	97.9	20.0	1.000007	
88000.0	20.0	-47.4	0.	-0. **	30.9	585.1	98.4	20.2	1.000007	
88500.0	19.6	-46.8	0.	-0. **	30.1	585.8	96.0	20.1	1.000007	
89000.0	19.1	-46.3	0.	-0. **	29.4	586.5	93.7	20.0	1.000007	
89500.0	18.7	-45.8	0.	-0. **	28.7	587.2	91.3	19.9	1.000006	
90000.0	18.3	-45.2	0.	-0. **	27.9	587.9	87.4	20.7	1.000006	
90500.0	17.9	-44.7	0.	-0. **	27.2	588.5	83.6	21.5	1.000006	
91000.0	17.5	-44.2	0.	-0. **	26.6	589.2	79.8	22.4	1.000006	
91500.0	17.1	-44.1	0.	-0. **	26.0	589.3	78.1	23.2	1.000006	
92000.0	16.7	-44.0	0.	-0. **	25.4	589.4	76.7	24.0	1.000006	
92500.0	16.3	-43.9	0.	-0. **	24.8	589.5	75.2	24.8	1.000006	
93000.0	16.0	-43.8	0.	-0. **	24.3	589.6	76.0	24.7	1.000005	

\*\* AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL  
5 SEPT. 68 0300 HRS MDT  
ASCENSION NO. 722

UPPER AIR DATA  
0312003907  
WHITE SANDS SITE

WSTM SITE COORDINATES  
E 488.580 FEET  
N 185.045 FEET

TABLE VII (Cont)

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND		DIRECTION DEGREES(TN)	WIND DATA		INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE			KNOTS	KNOTS		SPEED KNOTS		
93500.0	15.6	-43.8	0.	-0. **	23.7	589.7	77.5	24.4	24.4	1.000005	
94000.0	15.3	-43.7	0.	-0. **	23.2	589.9	79.1	24.1	24.1	1.000005	
94500.0	14.9	-43.6	0.	-0. **	22.7	590.0	81.0	23.6	23.6	1.000005	
95000.0	14.6	-43.5	0.	-0. **	22.1	590.1	83.1	22.8	22.8	1.000005	
95500.0	14.3	-43.4	0.	-0. **	21.6	590.2	85.3	22.1	22.1	1.000005	
96000.0	14.0	-43.3	0.	-0. **	21.2	590.3	86.2	21.5	21.5	1.000005	
96500.0	13.6	-43.2	0.	-0. **	20.7	590.4	85.0	21.1	21.1	1.000005	
97000.0	13.3	-43.1	0.	-0. **	20.2	590.5	83.8	20.6	20.6	1.000005	
97500.0	13.0	-43.0	0.	-0. **	19.8	590.7	82.5	20.4	20.4	1.000004	
98000.0	12.8	-43.0	0.	-0. **	19.3	590.8	80.8	21.3	21.3	1.000004	
98500.0	12.5	-42.9	0.	-0. **	18.9	590.9	79.0	22.2	22.2	1.000004	
99000.0	12.2	-42.8	0.	-0. **	18.5	591.0	77.3	23.1	23.1	1.000004	
99500.0	11.9	-42.7	0.	-0. **	18.0	591.1	78.2	23.4	23.4	1.000004	
100000.0	11.7	-42.6	0.	-0. **	17.6	591.2	79.2	23.8	23.8	1.000004	
100500.0	11.4	-42.5	0.	-0. **	17.2	591.3	80.2	24.2	24.2	1.000004	
101000.0	11.2	-42.4	0.	-0. **	16.8	591.4	83.5	25.4	25.4	1.000004	
101500.0	10.9	-42.3	0.	-0. **	16.5	591.6	87.3	26.7	26.7	1.000004	
102000.0	10.7	-42.3	0.	-0. **	16.1	591.7	91.1	28.1	28.1	1.000004	
102500.0	10.4	-42.2	0.	-0. **	15.7	591.8	92.9	28.7	28.7	1.000004	
103000.0	10.2	-42.1	0.	-0. **	15.4	591.9	92.9	28.6	28.6	1.000003	
103500.0	10.0	-42.0	0.	-0. **	15.0	592.0	93.0	28.6	28.6	1.000003	
104000.0	9.8	-41.9	0.	-0. **	14.7	592.1	93.2	28.7	28.7	1.000003	
104500.0	9.5	-41.8	0.	-0. **	14.4	592.2	93.8	29.4	29.4	1.000003	
105000.0	9.3	-41.7	0.	-0. **	14.0	592.3	94.4	30.2	30.2	1.000003	
105500.0	9.1	-41.7	0.	-0. **	13.7	592.4	95.1	31.0	31.0	1.000003	
106000.0	8.9	-41.6	0.	-0. **	13.4	592.5	94.9	31.2	31.2	1.000003	
106500.0	8.7	-41.5	0.	-0. **	13.1	592.7	94.2	31.0	31.0	1.000003	
107000.0	8.5	-41.4	0.	-0. **	12.8	592.8	93.5	30.8	30.8	1.000003	
107500.0	8.4	-41.3	0.	-0. **	12.5	592.9	92.8	30.5	30.5	1.000003	
108000.0	8.2	-41.2	0.	-0. **	12.3	593.0	94.0	31.1	31.1	1.000003	

\*\* AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL  
5 SEPT. 68  
ASCENSION NO. 722

UPPER AIR DATA  
0312003907  
WHITE SANDS SITE

WSTM SITE COORDINATES  
E 488.580 FEET  
N 185.045 FEET

TABLE VII (Cont)

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA DIRECTION DEGREES(TN)	SPEED KNOTS	INDEX OF REFRACTION
108500.0	8.0	-41.1	-0. **	12.0	593.1	95.2	31.7	1.0000003
109000.0	7.8	-41.1	-0. **	11.7	593.2	96.4	32.3	1.0000003
109500.0	7.6	-41.0	-0. **	11.5	593.3	97.3	33.0	1.0000003
110000.0	7.5	-40.9	-0. **	11.2	593.4	97.8	33.9	1.0000002
110500.0	7.3	-40.8	-0. **	11.0	593.5	98.4	34.7	1.0000002
111000.0	7.1	-40.7	-0. **	10.7	593.6	98.9	35.5	1.0000002
111500.0	7.0	-40.6	-0. **	10.5	593.7			1.0000002
112000.0	6.8	-40.6	-0. **	10.2	593.8			1.0000002
112500.0	6.7	-40.5	-0. **	10.0	593.9			1.0000002
113000.0	6.5	-40.4	-0. **	9.8	594.1			1.0000002
113500.0	6.4	-40.3	-0. **	9.6	594.2			1.0000002
114000.0	6.3	-40.2	-0. **	9.4	594.3			1.0000002
114500.0	6.1	-40.1	-0. **	9.2	594.4			1.0000002
115000.0	6.0	-40.1	-0. **	8.9	594.5			1.0000002

\*\* AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

MANDATORY LEVELS  
0312003907  
WHITE SANDS SITE

WSTM SITE COORDINATES  
E 88.580 FEET  
N 185.045 FEET

STATION ALTITUDE 3989.0 FEET MSL  
5 SEPT. 68 0300 HRS MDT  
ASCENSION NO. 722

TABLE VIII

PRESSURE GEOPOTENTIAL		TEMPERATURE		REL. HUM.		WIND DATA	
MILLIBARS	FEET	AIR DEGREES	DEWPOINT CENTIGRADE	PERCENT		DIRECTION DEGREES(TN)	SPEED KNOTS
850.0	5019.	19.1	10.4	57.		143.4	7.6
800.0	6722.	16.1	8.1	59.		188.9	13.2
750.0	8520.	14.7	3.3	46.		212.0	11.2
700.0	10420.	10.0	0.3	51.		241.7	8.6
650.0	12425.	4.9	-2.9	57.		279.0	2.7
600.0	14545.	-1.4	-4.4	80.		8.7	6.2
550.0	16801.	-6.2	-11.3	68.		336.6	9.4
500.0	19241.	-9.4	-28.0	21.		300.1	15.0
450.0	21887.	-14.1	-33.3	18.		317.8	16.6
400.0	24779.	-21.4	-39.0	19.		307.7	18.3
350.0	27959.	-29.3	-45.4	20.		298.1	23.0
300.0	31505.	-38.2	-55.3	15.**		296.1	26.7
250.0	35532.	-48.4	-88.2	0.**		284.9	34.6
200.0	40248.	-57.0	0.	-0.**		261.5	41.6
175.0	42998.	-60.6	0.	-0.**		269.4	41.1
150.0	46117.	-64.6	0.	-0.**		260.6	31.0
125.0	49765.	-65.8	0.	-0.**		269.1	24.2
100.0	54185.	-63.7	0.	-0.**		256.2	12.3
80.0	58690.	-62.4	0.	-0.**		254.0	8.8
70.0	61399.	-61.7	0.	-0.**		223.8	8.3
60.0	64538.	-60.8	0.	-0.**		199.5	7.9
50.0	68273.	-58.6	0.	-0.**		296.0	6.6
40.0	72919.	-54.5	0.	-0.**		59.7	12.1
30.0	78986.	-52.5	0.	-0.**		84.6	25.2
25.0	82855.	-51.8	0.	-0.**		97.2	19.1
20.0	87642.	-47.3	0.	-0.**		98.3	20.2
15.0	93956.	-43.6	0.	-0.**		80.4	23.7
10.0	102932.	-42.0	0.	-0.**		93.0	28.6
7.0	110878.	-40.6	0.	-0.**			

\*\* AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL  
5 SEPT.68  
ASCENSION NO. 72  
0530 HRS MDT

SIGNIFICANT LEVEL DATA  
0295003905  
WHITE SANDS SITE

WSTM SITE COORDINATES  
E 488,580 FEET  
N 185,045 FEET

TABLE IX

PRESSURE GEOMETRIC ALTITUDE		TEMPERATURE		REL. HUM.
HILLIBARS	MSL FEET	AIR DEGREES	DEWPOINT CENTIGRADE	
881.7	3989.0	18.0	13.6	75.0
872.0	4301.0	18.5	11.9	65.0
850.0	5022.9	19.1	12.5	65.0
801.0	6692.5	15.8	10.2	69.0
765.0	7977.7	16.2	3.3	42.0
733.0	9166.3	13.8	-0.3	38.0
659.0	12071.8	5.7	-2.2	57.0
609.0	14172.9	-0.2	-4.7	72.0
589.0	15049.5	-2.0	-7.7	65.0
578.0	15541.7	-3.1	-6.9	75.0
571.0	15859.6	-2.2	-17.9	29.0
543.0	17166.5	-4.5	-28.1	14.0
484.0	20108.8	-10.7	-28.4	22.0
481.0	20266.1	-10.7	-26.2	27.0
475.0	20583.6	-10.6	-31.6	16.0
398.0	24964.5	-21.5	-37.6	22.0
315.0	30481.1	-35.3	-49.2	23.0
240.0	36515.2	-50.7	0.	-0. **
224.0	37986.7	-53.4	0.	-0. **
190.0	41439.6	-58.1	0.	-0. **
175.0	43132.5	-61.6	0.	-0. **
167.0	44086.6	-62.2	0.	-0. **
162.0	44703.5	-63.7	0.	-0. **
136.0	48240.8	-63.7	0.	-0. **
113.0	51941.8	-68.9	0.	-0. **
89.0	56732.4	-62.0	0.	-0. **
60.0	64849.6	-58.3	0.	-0. **
30.0	79452.1	-52.4	0.	-0. **
23.0	85251.8	-43.2	0.	-0. **
20.0	88350.9	-45.5	0.	-0. **

\*\* RELATIVE HUMIDITY NOT SUPPLIED. ZERO VALUE ASSUMED FOR COMPUTATIONS.



STATION ALTITUDE 3989.0 FEET MSL  
 5 SEPT.68 0530 HRS MDT  
 ASCENSION NO. 723

SIGNIFICANT LEVEL DATA  
 0295003905  
 WHITE SANDS SITE

WSTM SITE COORDINATES  
 E 488,580 FEET  
 N 185,045 FEET

TABLE IX (Cont)

PRESSURE GEOMETRIC ALTITUDE MILLIBARS MSL FEET	TEMPERATURE		REL. HUM. PERCENT
	AIR DEGREES	DEWPOINT CENTIGRADE	
13.0 97859.9	-45.4	0.	-0. **
6.4 113826.3	-36.5	0.	-0. **

\*\* RELATIVE HUMIDITY NOT SUPPLIED. ZERO VALUE ASSUMED FOR COMPUTATIONS.

STATION ALTITUDE 3989.0 FEET MSL  
5 SEPT.68  
ASCENSION NO. 723

UPPER AIR DATA  
0295003905  
WHITE SANDS SITE

WSTM SITE COORDINATES  
E 488,580 FEET  
N 185,045 FEET

TABLE X

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND		WIND DATA		INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE			KNOTS	KNOTS	DIRECTION DEGREES(TN)	SPEED KNOTS	
3989.0	881.7	18.0	13.6	75.0	1048.1	666.6	300.0	300.0	3.1	1.000303
4000.0	881.4	18.0	13.5	74.6	1047.7	666.6	299.4	299.4	3.1	1.000302
4500.0	865.9	18.7	12.0	65.0	1027.5	667.2	272.6	272.6	4.6	1.000291
5000.0	850.7	19.1	12.4	65.0	1007.8	667.8	245.8	245.8	6.0	1.000288
5500.0	835.7	18.2	11.8	66.1	993.3	666.7	219.1	219.1	7.4	1.000283
6000.0	821.0	17.2	11.1	67.3	979.3	665.5	192.3	192.3	8.9	1.000278
6500.0	806.5	16.2	10.5	68.5	965.5	664.3	179.3	179.3	9.6	1.000272
7000.0	792.2	15.9	8.8	62.5	949.8	663.8	187.5	187.5	9.2	1.000263
7500.0	778.2	16.1	6.3	52.0	933.2	663.7	200.5	200.5	8.7	1.000251
8000.0	764.4	16.2	3.2	41.9	917.1	663.6	217.8	217.8	8.1	1.000239
8500.0	750.8	15.1	1.8	40.2	904.2	662.3	230.1	230.1	8.1	1.000233
9000.0	737.4	14.1	0.2	38.6	891.5	661.0	239.5	239.5	8.3	1.000227
9500.0	724.1	12.9	-0.3	40.2	879.3	659.5	246.0	246.0	9.2	1.000224
10000.0	711.0	11.5	-0.5	43.5	867.6	657.9	251.1	251.1	10.3	1.000221
10500.0	698.1	10.1	-0.8	46.7	856.0	656.3	253.7	253.7	9.8	1.000218
11000.0	685.4	8.7	-1.1	50.0	844.7	654.7	255.2	255.2	8.7	1.000215
11500.0	672.9	7.3	-1.6	53.3	833.5	653.1	262.5	262.5	7.5	1.000212
12000.0	660.7	5.9	-2.1	56.5	822.5	651.4	272.6	272.6	6.3	1.000209
12500.0	648.5	4.5	-2.6	60.1	811.4	649.8	293.2	293.2	4.6	1.000206
13000.0	636.4	3.1	-3.1	63.6	800.4	648.1	319.1	319.1	2.7	1.000202
13500.0	624.6	1.7	-3.8	67.2	789.6	646.4	337.6	337.6	2.3	1.000199
14000.0	613.0	0.3	-4.4	70.8	778.9	644.7	354.0	354.0	2.3	1.000196
14500.0	601.5	-0.9	-5.8	69.4	767.7	643.3	338.3	338.3	2.6	1.000191
15000.0	590.1	-1.9	-7.6	65.4	756.3	642.0	323.0	323.0	2.8	1.000186
15500.0	578.9	-3.0	-7.0	74.2	744.9	640.7	317.1	317.1	3.5	1.000185
16000.0	567.9	-2.4	-18.8	27.4	730.3	640.9	316.3	316.3	4.7	1.000170
16500.0	557.1	-3.3	-22.3	21.6	718.9	639.8	323.4	323.4	6.4	1.000165
17000.0	546.5	-4.2	-26.4	15.9	707.6	638.7	325.9	325.9	8.3	1.000161
17500.0	536.0	-5.2	-28.0	14.9	696.6	637.5	324.9	324.9	10.1	1.000158
18000.0	525.6	-6.3	-27.9	16.3	685.8	636.3	323.3	323.3	11.6	1.000156

STATION ALTITUDE 3989.0 FEET MSL  
5 SEPT.68 0530 HRS MDT  
ASCENSION NO. 723

UPPER AIR DATA  
0295003905  
WHITE SANDS SITE  
TABLE X (Cont)

WSTM SITE COORDINATES  
E 488,580 FEET  
N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL.HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND		WIND DATA		INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE			KNOTS	KNOTS	DIRECTION DEGREES(TN)	SPEED KNOTS	
18500.0	515.4	-7.3	-27.9	17.6	675.2	635.0		321.4	12.9	1.000154
19000.0	505.4	-8.4	-28.0	19.0	664.8	633.8		318.0	13.8	1.000151
19500.0	495.7	-9.4	-28.1	20.3	654.5	632.5		313.9	14.5	1.000149
20000.0	486.1	-10.5	-28.3	21.7	644.4	631.2		313.0	14.2	1.000147
20500.0	476.6	-10.6	-29.9	18.9	632.2	631.0		312.8	13.7	1.000144
21000.0	467.1	-11.6	-32.1	16.6	622.1	629.8		312.3	13.3	1.000141
21500.0	457.7	-12.9	-32.8	17.3	612.6	628.3		311.8	13.1	1.000139
22000.0	448.6	-14.1	-33.4	17.9	603.2	626.8		311.4	13.2	1.000136
22500.0	439.6	-15.4	-34.1	18.6	594.0	625.3		311.4	13.7	1.000134
23000.0	430.9	-16.6	-34.8	19.3	585.0	623.7		312.1	14.9	1.000132
23500.0	422.2	-17.9	-35.5	20.0	576.1	622.2		313.0	16.3	1.000130
24000.0	413.8	-19.1	-36.2	20.7	567.4	620.7		314.0	17.9	1.000128
24500.0	405.5	-20.3	-36.9	21.4	558.8	619.2		314.7	18.8	1.000126
25000.0	397.4	-21.6	-37.7	22.0	550.3	617.6		315.4	19.3	1.000124
25500.0	389.1	-22.8	-38.8	22.1	541.4	616.1		315.9	19.3	1.000122
26000.0	380.9	-24.1	-39.8	22.2	532.8	614.6		316.4	19.3	1.000120
26500.0	372.9	-25.3	-40.8	22.3	524.2	613.0		315.9	19.3	1.000118
27000.0	365.1	-26.6	-41.9	22.4	515.8	611.5		315.3	19.3	1.000116
27500.0	357.4	-27.8	-42.9	22.5	507.6	609.9		313.6	20.2	1.000114
28000.0	349.9	-29.1	-44.0	22.6	499.5	608.3		311.8	21.3	1.000112
28500.0	342.6	-30.2	-45.0	22.6	491.6	606.8		309.6	22.0	1.000110
29000.0	335.4	-31.6	-46.1	22.7	483.7	605.2		307.3	22.7	1.000108
29500.0	328.4	-32.8	-47.1	22.8	476.1	603.6		305.5	23.0	1.000107
30000.0	321.5	-34.1	-48.2	22.9	468.5	602.1		303.9	23.4	1.000105
30500.0	314.7	-35.3	-49.3	22.9**	461.1	600.5		302.6	24.1	1.000103
31000.0	307.7	-36.6	-51.1	21.0**	453.3	598.9		301.4	25.0	1.000101
31500.0	300.9	-37.9	-53.0	19.1**	445.6	597.2		297.8	26.1	1.000100
32000.0	294.2	-39.2	-55.0	17.2**	438.0	595.6		293.9	27.3	1.000098
32500.0	287.6	-40.5	-57.0	15.3**	430.6	594.0		289.7	28.6	1.000096
33000.0	281.2	-41.7	-59.1	13.4**	423.3	592.4		285.4	29.8	1.000094

\*\* AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL  
5 SEPT. 68 0530 HRS MDT  
ASCENSION NO. 723

UPPER AIR DATA  
0295003905  
WHITE SANDS SITE

WSTM SITE COORDINATES  
E 488,580 FEET  
N 185,045 FEET

TABLE X (Cont)

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND		WIND DATA		INDEX QF
		AIR DEGREES	DEWPOINT CENTIGRADE			KNOTS	KNOTS	DIRECTION DEGREES(TN)	SPEED KNOTS	
33500.0	274.9	-43.0	-61.4	11.5**	416.2	590.7	279.9	279.9	29.6	1.000093
34000.0	268.8	-44.3	-63.8	9.6**	409.2	589.1	274.5	274.5	29.4	1.000091
34500.0	262.8	-45.6	-66.4	7.7**	402.3	587.4	272.5	272.5	30.1	1.000090
35000.0	257.0	-46.8	-69.5	5.8**	395.6	585.8	270.5	270.5	30.8	1.000088
35500.0	251.2	-48.1	-73.1	3.9**	389.0	584.1	269.1	269.1	31.2	1.000087
36000.0	245.6	-49.4	-78.4	2.0**	382.5	582.5	267.8	267.8	31.7	1.000085
36500.0	240.2	-50.7	-98.3	0.1**	376.1	580.8	268.3	268.3	33.6	1.000084
37000.0	234.6	-51.6	0.	-0. **	368.9	579.6	268.8	268.8	35.3	1.000082
37500.0	229.2	-52.5	0.	-0. **	361.9	578.4	267.7	267.7	34.4	1.000081
38000.0	223.9	-53.4	0.	-0. **	355.0	577.2	266.6	266.6	33.5	1.000079
38500.0	218.6	-54.1	0.	-0. **	347.7	576.3	265.3	265.3	33.7	1.000077
39000.0	213.4	-54.8	0.	-0. **	340.5	575.4	264.1	264.1	34.0	1.000076
39500.0	208.4	-55.5	0.	-0. **	333.6	574.5	262.6	262.6	35.1	1.000074
40000.0	203.5	-56.1	0.	-0. **	326.7	573.6	261.2	261.2	36.4	1.000073
40500.0	198.7	-56.8	0.	-0. **	320.0	572.7	261.2	261.2	38.2	1.000071
41000.0	194.0	-57.5	0.	-0. **	313.5	571.8	261.3	261.3	40.1	1.000070
41500.0	189.4	-58.2	0.	-0. **	307.1	570.8	262.4	262.4	40.7	1.000068
42000.0	184.9	-59.3	0.	-0. **	301.2	569.5	263.5	263.5	41.2	1.000067
42500.0	180.5	-60.3	0.	-0. **	295.4	568.1	265.1	265.1	39.5	1.000066
43000.0	176.1	-61.3	0.	-0. **	289.7	566.7	266.7	266.7	37.3	1.000065
43500.0	171.9	-61.8	0.	-0. **	283.4	566.0	268.0	268.0	36.0	1.000063
44000.0	167.7	-62.1	0.	-0. **	276.9	565.6	269.2	269.2	35.1	1.000062
44500.0	163.6	-63.2	0.	-0. **	271.6	564.2	268.9	268.9	34.0	1.000060
45000.0	159.6	-63.7	0.	-0. **	265.6	563.5	267.7	267.7	32.9	1.000059
45500.0	155.7	-63.7	0.	-0. **	259.1	563.5	265.8	265.8	32.2	1.000058
46000.0	151.9	-63.7	0.	-0. **	252.7	563.5	263.4	263.4	31.9	1.000056
46500.0	148.2	-63.7	0.	-0. **	246.6	563.5	262.0	262.0	30.8	1.000055
47000.0	144.6	-63.7	0.	-0. **	240.5	563.5	261.2	261.2	29.1	1.000054
47500.0	141.1	-63.7	0.	-0. **	234.7	563.5	261.2	261.2	27.6	1.000052
48000.0	137.6	-63.7	0.	-0. **	228.9	563.5	262.1	262.1	26.2	1.000051

\*\* AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL  
5 SEPT.68  
ASCENSION NO. 723

UPPER AIR DATA  
0295003905  
WHITE SANDS SITE

WSTM SITE COORDINATES  
E 488,580 FEET  
N 185,045 FEET

TABLE X (Cont)

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL.HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND		WIND DATA DIRECTION DEGREES(TN)	SPEED KNOTS	INDEX OF REFRACTION
		AIR DEGREES CENTIGRADE	DEWPOINT CENTIGRADE			KNOTS	KNOTS			
48500.0	134.2	-64.1	0.	-0. **	223.7	563.0	263.7	263.7	24.7	1.000050
49000.0	130.9	-64.8	0.	-0. **	218.9	562.1	264.6	264.6	23.1	1.000049
49500.0	127.7	-65.5	0.	-0. **	214.2	561.1	268.9	268.9	21.7	1.000048
50000.0	124.5	-66.2	0.	-0. **	209.6	560.2	268.3	268.3	21.2	1.000047
50500.0	121.5	-66.9	0.	-0. **	205.1	559.2	267.8	267.8	20.8	1.000046
51000.0	118.5	-67.6	0.	-0. **	200.8	558.3	267.8	267.8	20.0	1.000045
51500.0	115.5	-68.3	0.	-0. **	196.5	557.3	267.7	267.7	19.2	1.000044
52000.0	112.7	-68.8	0.	-0. **	192.1	556.6	267.0	267.0	19.1	1.000043
52500.0	109.9	-68.1	0.	-0. **	186.7	557.6	266.2	266.2	19.1	1.000042
53000.0	107.2	-67.4	0.	-0. **	181.5	558.6	270.5	270.5	18.7	1.000040
53500.0	104.6	-66.7	0.	-0. **	176.4	559.5	277.8	277.8	18.1	1.000039
54000.0	102.0	-65.9	0.	-0. **	171.5	560.5	281.6	281.6	17.9	1.000038
54500.0	99.5	-65.2	0.	-0. **	166.7	561.5	281.4	281.4	18.3	1.000037
55000.0	97.0	-64.5	0.	-0. **	162.0	562.5	281.3	281.3	18.6	1.000036
55500.0	94.6	-63.8	0.	-0. **	157.5	563.4	281.3	281.3	18.3	1.000035
56000.0	92.3	-63.1	0.	-0. **	153.1	564.4	279.6	279.6	18.0	1.000034
56500.0	90.0	-62.3	0.	-0. **	148.8	565.4	259.9	259.9	17.2	1.000033
57000.0	87.9	-61.9	0.	-0. **	144.9	566.0	240.3	240.3	16.3	1.000032
57500.0	85.7	-61.7	0.	-0. **	141.2	566.3	242.7	242.7	15.2	1.000031
58000.0	83.7	-61.4	0.	-0. **	137.7	566.6	248.6	248.6	14.1	1.000031
58500.0	81.7	-61.2	0.	-0. **	134.3	566.9	254.1	254.1	13.4	1.000030
59000.0	79.7	-61.0	0.	-0. **	130.9	567.2	259.2	259.2	13.1	1.000029
59500.0	77.8	-60.7	0.	-0. **	127.6	567.5	268.7	268.7	12.4	1.000028
60000.0	75.9	-60.5	0.	-0. **	124.4	567.8	285.3	285.3	11.4	1.000028
60500.0	74.1	-60.3	0.	-0. **	121.3	568.1	297.3	297.3	9.8	1.000027
61000.0	72.3	-60.1	0.	-0. **	118.3	568.4	287.4	287.4	5.4	1.000026
61500.0	70.6	-59.8	0.	-0. **	115.3	568.7	277.5	277.5	1.1	1.000026
62000.0	68.9	-59.6	0.	-0. **	112.4	569.0	213.9	213.9	3.2	1.000025
62500.0	67.3	-59.4	0.	-0. **	109.6	569.3	147.6	147.6	5.7	1.000024
63000.0	65.6	-59.1	0.	-0. **	106.9	569.6	128.7	128.7	6.2	1.000024

\*\* AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL  
5 SEPT.68 .0530 HRS MDT  
ASCENSION NO. 723

UPPER AIR DATA  
0295003905  
WHITE SANDS SITE

WSTM SITE COORDINATES  
E 488,580 FEET  
N 185,045 FEET

TABLE X (Cont)

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND		WIND DATA DIRECTION DEGREES(TN)	SPEED KNOTS	INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE			KNOTS	KNOTS			
63500.0	64.1	-58.9	0.	-0. **	104.2	569.9		127.0	5.9	1.000023
64000.0	62.5	-58.7	0.	-0. **	101.6	570.2		102.4	4.6	1.000023
64500.0	61.0	-58.5	0.	-0. **	99.0	570.5		57.0	2.2	1.000022
65000.0	59.6	-58.2	0.	-0. **	96.6	570.8		29.7	1.4	1.000022
65500.0	58.2	-58.0	0.	-0. **	94.2	571.1		41.6	4.0	1.000021
66000.0	56.8	-57.8	0.	-0. **	91.9	571.4		53.1	6.7	1.000020
66500.0	55.5	-57.6	0.	-0. **	89.7	571.6		59.8	9.3	1.000020
67000.0	54.2	-57.4	0.	-0. **	87.5	571.9		66.5	11.9	1.000019
67500.0	52.9	-57.2	0.	-0. **	85.4	572.2		71.7	14.8	1.000019
68000.0	51.7	-57.0	0.	-0. **	83.3	572.4		76.7	17.6	1.000019
68500.0	50.5	-56.8	0.	-0. **	81.3	572.7		82.0	18.6	1.000018
69000.0	49.3	-56.6	0.	-0. **	79.3	573.0		87.4	18.3	1.000018
69500.0	48.1	-56.4	0.	-0. **	77.4	573.2		90.9	18.0	1.000017
70000.0	47.0	-56.2	0.	-0. **	75.5	573.5		90.9	17.5	1.000017
70500.0	45.9	-56.0	0.	-0. **	73.6	573.8		90.8	17.0	1.000016
71000.0	44.8	-55.8	0.	-0. **	71.8	574.0		91.1	17.1	1.000016
71500.0	43.8	-55.6	0.	-0. **	70.1	574.3		91.4	17.3	1.000016
72000.0	42.7	-55.4	0.	-0. **	68.4	574.6		88.4	20.4	1.000015
72500.0	41.7	-55.2	0.	-0. **	66.7	574.8		83.8	25.2	1.000015
73000.0	40.8	-55.0	0.	-0. **	65.1	575.1		79.9	27.5	1.000014
73500.0	39.8	-54.8	0.	-0. **	63.5	575.4		78.3	23.2	1.000014
74000.0	38.9	-54.6	0.	-0. **	62.0	575.6		76.7	18.9	1.000014
74500.0	37.9	-54.4	0.	-0. **	60.4	575.9		78.1	20.2	1.000013
75000.0	37.1	-54.2	0.	-0. **	59.0	576.2		80.0	22.2	1.000013
75500.0	36.2	-54.0	0.	-0. **	57.5	576.4		82.1	20.7	1.000013
76000.0	35.3	-53.8	0.	-0. **	56.1	576.7		84.4	15.2	1.000012
76500.0	34.5	-53.6	0.	-0. **	54.8	577.0		86.5	10.4	1.000012
77000.0	33.7	-53.4	0.	-0. **	53.4	577.2		86.4	13.6	1.000012
77500.0	32.9	-53.2	0.	-0. **	52.1	577.5		86.3	16.9	1.000012
78000.0	32.1	-53.0	0.	-0. **	50.9	577.8		83.4	15.9	1.000011

\*\* AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL  
5 SEPT. 68  
ASCENSION NO. 723

UPPER AIR DATA  
0295003905  
WHITE SANDS SITE

WSTM SITE COORDINATES  
E 488,580 FEET  
N 185,045 FEET

TABLE X (Cont)

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA DIRECTION DEGREES(TN)	SPEED KNOTS	INDEX OF REFRACTION
78500.0	31.4	-52.8	-0. **	49.6	578.0	79.1	13.1	1.000011
79000.0	30.7	-52.6	-0. **	48.4	578.3	75.7	11.2	1.000011
79500.0	29.9	-52.3	-0. **	47.2	578.6	74.2	11.5	1.000011
80000.0	29.3	-51.5	-0. **	46.0	579.7	72.6	11.8	1.000010
80500.0	28.6	-50.7	-0. **	44.8	580.7	70.8	12.1	1.000010
81000.0	27.9	-49.9	-0. **	43.6	581.7	68.1	12.3	1.000010
81500.0	27.3	-49.2	-0. **	42.5	582.8	65.4	12.4	1.000009
82000.0	26.7	-48.4	-0. **	41.4	583.8	62.8	12.6	1.000009
82500.0	26.1	-47.6	-0. **	40.3	584.8	63.3	13.2	1.000009
83000.0	25.5	-46.8	-0. **	39.2	585.9	65.6	14.1	1.000009
83500.0	24.9	-46.0	-0. **	38.2	586.9	67.9	15.0	1.000009
84000.0	24.4	-45.2	-0. **	37.2	587.9	70.3	15.9	1.000008
84500.0	23.8	-44.4	-0. **	36.3	588.9	72.4	15.6	1.000008
85000.0	23.3	-43.6	-0. **	35.3	589.9	74.5	15.3	1.000008
85500.0	22.7	-43.4	-0. **	34.5	590.2	76.5	15.0	1.000008
86000.0	22.2	-43.8	-0. **	33.8	589.7	78.2	15.2	1.000008
86500.0	21.7	-44.1	-0. **	33.1	589.3	79.0	16.7	1.000007
87000.0	21.3	-44.5	-0. **	32.4	588.8	79.8	18.1	1.000007
87500.0	20.8	-44.9	-0. **	31.7	588.3	80.6	19.5	1.000007
88000.0	20.3	-45.2	-0. **	31.1	587.8	80.3	20.1	1.000007
88500.0	19.9	-45.5	-0. **	30.4	587.5	79.3	20.1	1.000007
89000.0	19.4	-45.5	-0. **	29.7	587.5	78.4	20.1	1.000007
89500.0	19.0	-45.5	-0. **	29.1	587.5	77.4	20.2	1.000006
90000.0	18.6	-45.5	-0. **	28.4	587.5	78.3	21.8	1.000006
90500.0	18.1	-45.5	-0. **	27.8	587.5	79.4	23.6	1.000006
91000.0	17.7	-45.5	-0. **	27.1	587.5	80.5	25.4	1.000006
91500.0	17.3	-45.5	-0. **	26.5	587.5	82.1	26.7	1.000006
92000.0	17.0	-45.5	-0. **	25.9	587.5	85.4	26.5	1.000006
92500.0	16.6	-45.5	-0. **	25.4	587.6	88.8	26.3	1.000006
93000.0	16.2	-45.5	-0. **	24.8	587.6	92.2	26.1	1.000006

\*\* AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL  
5 SEPT. 68  
ASCENSION NO. 723

UPPER AIR DATA  
0295003905  
WHITE SANDS SITE

WSTM SITE COORDINATES  
E 488,580 FEET  
N 185,045 FEET

TABLE X (Cont).

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND		WIND DATA DIRECTION DEGREES(TN)	SPEED KNOTS	INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE			KNOTS	KNOTS			
93500.0	15.8	-45.4	0.	-0. **	24.2	587.6		94.0	26.0	1.000005
94000.0	15.5	-45.4	0.	-0. **	23.7	587.6		94.6	26.0	1.000005
94500.0	15.1	-45.4	0.	-0. **	23.2	587.6		95.2	26.0	1.000005
95000.0	14.8	-45.4	0.	-0. **	22.6	587.6		95.8	26.0	1.000005
95500.0	14.5	-45.4	0.	-0. **	22.1	587.6		94.5	25.8	1.000005
96000.0	14.1	-45.4	0.	-0. **	21.6	587.6		93.0	25.7	1.000005
96500.0	13.8	-45.4	0.	-0. **	21.2	587.6		91.4	25.5	1.000005
97000.0	13.5	-45.4	0.	-0. **	20.7	587.6		89.6	25.4	1.000005
97500.0	13.2	-45.4	0.	-0. **	20.2	587.6		86.5	25.5	1.000005
98000.0	12.9	-45.3	0.	-0. **	19.8	587.7		83.3	25.6	1.000005
98500.0	12.6	-45.0	0.	-0. **	19.3	588.1		80.2	25.6	1.000004
99000.0	12.4	-44.8	0.	-0. **	18.9	588.4		78.4	26.1	1.000004
99500.0	12.1	-44.5	0.	-0. **	18.4	588.8		78.1	26.9	1.000004
100000.0	11.8	-44.2	0.	-0. **	18.0	589.2		77.9	27.7	1.000004
100500.0	11.6	-43.9	0.	-0. **	17.6	589.5		77.6	28.5	1.000004
101000.0	11.3	-43.6	0.	-0. **	17.2	589.9		78.2	28.7	1.000004
101500.0	11.1	-43.4	0.	-0. **	16.8	590.2		79.2	28.6	1.000004
102000.0	10.8	-43.1	0.	-0. **	16.4	590.6		80.1	28.5	1.000004
102500.0	10.6	-42.8	0.	-0. **	16.0	591.0		81.0	28.4	1.000004
103000.0	10.3	-42.5	0.	-0. **	15.6	591.3		80.1	28.1	1.000003
103500.0	10.1	-42.3	0.	-0. **	15.3	591.7		79.0	27.8	1.000003
104000.0	9.9	-42.0	0.	-0. **	14.9	592.0		77.9	27.5	1.000003
104500.0	9.7	-41.7	0.	-0. **	14.6	592.4		77.5	27.4	1.000003
105000.0	9.5	-41.4	0.	-0. **	14.2	592.7		80.1	27.7	1.000003
105500.0	9.3	-41.1	0.	-0. **	13.9	593.1		82.7	28.1	1.000003
106000.0	9.1	-40.9	0.	-0. **	13.6	593.5		85.2	28.5	1.000003
106500.0	8.9	-40.6	0.	-0. **	13.3	593.8		86.8	29.1	1.000003
107000.0	8.7	-40.3	0.	-0. **	13.0	594.2		87.5	29.8	1.000003
107500.0	8.5	-40.0	0.	-0. **	12.7	594.5		88.2	30.6	1.000003
108000.0	8.3	-39.7	0.	-0. **	12.4	594.9		89.0	31.5	1.000003

\*\* AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.



STATION ALTITUDE 3989.0 FEET MSL  
5 SEPT.68 0530 HRS MDT  
ASCENSION NO. 723

UPPER AIR DATA  
0295003905  
WHITE SANDS SITE

WSTM SITE COORDINATES  
E 488,580 FEET  
N 185,045 FEET

TABLE X (Cont)

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE		REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND		WIND DATA		INDEX OF REFRACTION
		AIR DEGREES	DEWPOINT CENTIGRADE			KNOTS	KNOTS	DIRECTION DEGREES(TN)	SPEED KNOTS	
108500.0	8.1	-39.5	0.	-0. **	12.1	595.2		94.9	42.1	1.000003
109000.0	7.9	-39.2	0.	-0. **	11.8	595.6		100.9	52.8	1.000003
109500.0	7.8	-38.9	0.	-0. **	11.5	595.9		106.8	63.4	1.000003
110000.0	7.6	-38.6	0.	-0. **	11.3	596.3				1.000003
110500.0	7.4	-38.4	0.	-0. **	11.0	596.6				1.000002
111000.0	7.3	-38.1	0.	-0. **	10.8	597.0				1.000002
111500.0	7.1	-37.8	0.	-0. **	10.5	597.4				1.000002
112000.0	6.9	-37.5	0.	-0. **	10.3	597.7				1.000002
112500.0	6.8	-37.2	0.	-0. **	10.0	598.1				1.000002
113000.0	6.6	-37.0	0.	-0. **	9.8	598.4				1.000002
113500.0	6.5	-36.7	0.	-0. **	9.6	598.8				1.000002

\*\* AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL  
5 SEPT. 68  
ASCENSION NO. 723

MANDATORY LEVELS  
0295003905  
WHITE SANDS SITE

WSTM SITE COORDINATES  
E 488,500 FEET  
N 185,045 FEET

TABLE XI

PRESSURE GEOPOTENTIAL		TEMPERATURE		REL. HUM. PERCENT	WIND DATA	
MILLIBARS	FEET	AIR DEGREES	DEWPOINT CENTIGRADE		DIRECTION DEGREES(TN)	SPEED KNOTS
850.0	5021.	19.1	12.5	65.	244.6	6.1
800.0	6725.	15.8	10.1	68.	183.0	9.4
750.0	8525.	15.1	1.7	40.	230.7	8.1
700.0	10427.	10.3	-0.7	46.	253.5	10.0
650.0	12432.	4.7	-2.5	60.	290.1	4.8
600.0	14552.	-1.0	-6.0	69.	336.2	2.6
550.0	16818.	-3.9	-24.9	18.	326.3	7.6
500.0	19263.	-8.9	-28.0	20.	315.7	14.2
450.0	21916.	-13.9	-33.3	18.	311.4	13.2
400.0	24809.	-21.2	-37.5	22.	315.2	19.1
350.0	27992.	-29.1	-44.0	23.	311.7	21.4
300.0	31541.	-38.1	-53.3	19.**	297.1	26.3
250.0	35570.	-48.4	-74.1	3.**	268.8	31.3
200.0	40289.	-56.6	0.	-0.**	261.2	37.7
175.0	43038.	-61.6	0.	-0.**	267.1	36.8
150.0	46151.	-63.7	0.	-0.**	262.4	31.6
125.0	49811.	-66.1	0.	-0.**	268.4	21.3
100.0	54226.	-65.4	0.	-0.**	281.4	18.2
80.0	58740.	-61.0	0.	-0.**	258.2	13.1
70.0	61470.	-59.7	0.	-0.**	260.2	1.5
60.0	64642.	-58.3	0.	-0.**	26.0	0.6
50.0	68420.	-56.7	0.	-0.**	83.6	18.5
40.0	73081.	-54.8	0.	-0.**	78.8	24.6
30.0	79150.	-52.4	0.	-0.**	74.3	11.5
25.0	83073.	-46.1	0.	-0.**	67.5	14.8
20.0	87977.	-45.5	0.	-0.**	79.6	20.1
15.0	94272.	-45.4	0.	-0.**	95.4	26.0
10.0	103187.	-42.1	0.	-0.**	78.6	27.7
7.0	111183.	-37.6	0.	-0.**		

\*\* AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

RELEASE TIME (MDT)		SECOND-STAGE IMPACT DISPLACEMENT IN MILES DUE TO WIND								AZI- MUTH (DEG- REES)	THEORETICAL IMPACT FROM LAUNCHER (IN MILES)		
		15-216 FT		216-4000 FT		4000-69330 FT		TOTAL					
RAWIN- SONDE	PIBAL	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	RANGE	N-S	E-W	
0300	0400	6.9S	9.0E	10.3S	10.1E	1.1S	20.1W	18.3S	1.0W	60.7	59.2N	13.4E	
0300	0430	4.9S	6.8E	14.0S	8.8E	1.1S	20.1W	20.0S	4.5W	58.3	57.5N	9.9E	
0300	0500	1.0S	2.6E	11.5S	4.9E	1.1S	20.1W	13.6S	12.6W	63.9	63.9N	1.8E	
0300	0515	0.3S	3.5W	10.0S	2.7E	1.1S	20.1W	11.4S	20.9W	66.4	66.1N	6.5W	
0300	0530	0.0	2.7W	7.2S	2.0E	1.1S	20.1W	8.3S	20.8W	69.5	69.2N	6.4W	
0300	0540	0.0	2.8W	5.8S	2.5E	1.1S	20.1W	6.9S	20.4W	70.9	70.6N	6.0W	
0300	0550	0.0	2.1W	6.4S	3.8E	1.1S	20.1W	7.5S	18.4W	70.1	70.0N	4.0W	
0530	0600*	0.7S	1.1W	7.6S	5.3E	3.5S	18.6W	11.8S	14.4W	65.7	65.7N	0.0	

\*Post-Shoot Data

\*\*Sonic Observation of the  
Trajectory and Impact of  
Missiles.

AZI- MUTH (DEG- REES)	MILES FROM LAUNCHER		
	RANGE	N-S	E-W
LAUNCHER SETTING (ELEVATION 84.5 DEGREES QE)	79.9	77.5N	19.3E
NO WIND IMPACT	78.8	77.5N	14.4E
PREDICTED SECOND-STAGE IMPACT	70.0	69.9N	3.7W
SECOND-STAGE IMPACT, SOTIM**	73.0	72.9N	3.8W
PREDICTED BOOSTER IMPACT	1.2	0.9N	0.8E
ACTUAL BOOSTER IMPACT	N/A	N/A	N/A

TABLE XII. IMPACT PREDICTION DATA  
NIKE-HYDAC STV, SR-073

UNCLASSIFIED

Security Classification

## DOCUMENT CONTROL DATA - R &amp; D .

(Security classification of this, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) U. S. Army Electronics Command Ft. Monmouth, New Jersey		2a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED	
		2b. GROUP	
3. REPORT TITLE  METEOROLOGICAL DATA REPORT, NIKE-HYDAC STV, SR-073			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)			
5. AUTHOR(S) (Last name, middle initial, first name)  Gordon L. Deazway			
6. REPORT DATE October 1968	7a. TOTAL NO. OF PAGES 36	7b. NO. OF REFS NONE	
8a. CONTRACT OR GRANT NO.		8b. ORIGINATOR'S REPORT NUMBER(S)	
9. PROJECT NO.		DR-358	
c. DA Task 17665702D127-02		9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
d.			
10. DISTRIBUTION STATEMENT This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of Atmospheric Science Research Office, White Sands Missile Range, New Mexico.			
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY U. S. Army Electronics Command Atmospheric Science Research Office White Sands Missile Range, New Mexico	
13. ABSTRACT  ➤ Meteorological data gathered for the launching of Nike-Hydac STV, SR-073, are presented for the Space and Missile Systems Organization and for ballistic studies. The data appear, along with calculated ballistic data, in tabular form.			

DD FORM 1473

REPLACES DD FORM 1473, 1 JAN 64, WHICH IS OBSOLETE FOR ARMY USE.

UNCLASSIFIED

Security Classification

UNCLASSIFIED

Security Classification

14.	KEY WORDS	LINK A		LINK B		LINK C	
		ROLE	WT	ROLE	WT	ROLE	WT
	1. Ballistics 2. Meteorology 3. Wind						

UNCLASSIFIED

Security Classification